



Deck-Drive™ DCSD COMPOSITE-TO-STEEL Screw



The DCSD Composite-to-steel screw is designed to easily drive through composite decking into 0.8–2.4 mm steel. The special cap head provides a clean, less noticeable installation and is available in 4 colours to suit composite timber.

Features

- Drives easily through 0.8–2.4 mm steel without predrilling
- Compact head provides a clean, finished deck surface with no mushrooming
- Available in 4 colours

Application

- Composite-to-steel decking
- Recommended steel thickness 0.8–2.4 mm
- Maximum recommended board thickness 25 mm

Finish

- Quik Guard® coating

Corrosion Resistance Level
MEDIUM

This screw is also available loose for hand-drive installation. See page 150 for details.



Cap head for a cleaner less noticeable fixing



Inverted upper threads clear excess material to ensure the screw is seated properly and consistently



Drill flute ejects composite material for easier installation

Collated Screws for the Quik Drive® System

10 Gauge Composite-to-Steel Screw

Bit(s) included with every box of screws

Model No.	Colour	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 250	PRO 300
DCSD238SBR01	Brown	4.9mm	60mm	16 TPI	#2 Drill Point	1000	#2 Undersize Square Drive	BIT2SU-RC10	✓	✓
DCSD238SGR01	Grey									
DCSD238SRD01	Red									
DCSD238STN02	Tan									

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.