



WSNTLG Timber Screw



WSNTLG timber screws are ideal for fastening subfloor, cladding, sill plates, stair treads and general exterior timber-to-timber applications using the Simpson Strong-Tie® Quik Drive® auto-feed screw driving system. The holding power of WSNTL screws reduces the gaps between the joist and subfloor that cause floor squeaks.

Features


- Flat head with nibs for easy countersinking
- #3 square drive (driver bit in each box)
- Twin lead
- Sharp point
- Curved collation

Application


- Exterior timber-to-timber
- Maximum recommended board thickness:
50 mm screw — 20 mm; 65 mm screw — 25 mm;
75 mm screw — 30 mm

Finish

- Class 3 Mechanically Galvanised



Flat head with nibs
for easy countersinking



Twin lead for better
clamping force



Sharp point for easy
starts into timber

Collated Screws for the Quik Drive® System

8 Gauge Timber Screw

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 200	PRO 250	PRO 300
WSNTLG2SA	4.5mm	50mm	Coarse Threads	Sharp Point	2000	#3 Undersize Square Drive	BIT3SU-RC10	✓		
WSNTLG212S		65mm			1500				✓	
WSNTLG3S		75mm			1000					

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.