



## CBSDHG Compressed Cement Sheet-to-Steel Screw



CBSDHG Compressed Cement Sheet Screw are ideal for fixing compressed fibre cement sheeting-to-steel joists. The CBSHDHG winged self-drilling screw requires no predrilling, making them easier and faster to install than standard winged self-drilling screws.

### Features

- Aggressive countersinking head for easy embedment
- #3 Square drive for ease of drive and torque — driver bits included
- Reinforced wings to cut clearance hole — no sheet ride
- Drill Point no predrilling required (1.2–3 mm steel)

### Application

- Cement sheeting/cladding-to-steel
- Maximum recommended board thickness:  
42 mm screw — 20 mm; 55 mm screw — 30 mm
- Recommended steel thickness 1.2–3 mm

### Finish

- Class 3 Galvanised



Countersinking head for clean finish



Wings to cut clearance hole means no sheet ride

Collated Screws for the Quik Drive® System

## 10 Gauge Compressed Cement Sheet-to-Steel Screw

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 200	PRO 250	PRO 300
CBSDHG158SA	4.9mm	42mm	16TPI	#2 Drill	1500	#3 square	BIT3S-RC10	—	✓	✓
CBSDHG214SA		55mm			1000					

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.