



DWFSD Drywall-to-CFS Screw



The DWFSD fastener with its fine thread and #2 drill point is ideal for drywall to cold-formed-steel applications. Available in lengths from 32 mm up to 60 mm to suit a diverse range of installation applications.

Features


- Bugle head
- #2 Phillips (driver bit in each box)
- Fine threads
- #2 drill point

Application


- Drywall to cold-formed steel
- Maximum recommended board thickness:
32 mm screw — 15 mm; 42 mm screw — 30 mm;
60 mm screw — 45 mm
- Recommended steel thickness 0.8–1.6 mm

Finish

- Class 3 N2000® Galvanised (DWFSDG114PS)
- Yellow Zinc



Bugle head for countersink finish in drywall



Fine thread perfect for embedment into cold form steel

6 and 8 Gauge Drywall-to-CFS Screw

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 200	PRO 250	PRO 300
DWFSDG114PS	3.5mm	32mm	20 TPI	#2 Drill	2500	#2 Phillips	BIT2P-RC10	✓	—	—
DWFZSD114PSA		42mm						—	—	
DWFZSD158PSA		60mm						—	—	
DWFZSD238PSA	4.2mm	60mm			1500		—	✓	✓	

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.